

CERTIFICATE OF COMPLIANCE

Certificate Number 20191120-E361658
Report Reference E361658-A6006-UL
Issue Date 2019-NOVEMBER-20

Issued to: Merryking Enterprises (HK) Co Ltd
OFFICE NO 3
10TH FL WITTY COMM BLDG
1A - 1L TUNG CHOI ST MONGKOK
KOWLOON HONG KONG

**This certificate confirms that
representative samples of**

POWER SUPPLIES FOR USE WITH AUDIO/VIDEO,
INFORMATION AND COMMUNICATION TECHNOLOGY
EQUIPMENT

See Addendum Page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 62368-1 and CAN/CSA C22.2 No. 62368-1-14 -
Audio/video, information and communication technology
equipment Part 1: Safety requirements

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20191120-E361658
Report Reference E361658-A6006-UL
Issue Date 2019-NOVEMBER-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

AC/DC Adapter

XSC-aaabbbbxyyz,MKC-aaabbbbxyyz, MKS-aaabbbbxyyz

aaa=030-400 indicate for output voltage 3.0Vdc - 40.0Vdc, minimum step is 0.1V, e.g.: 030 = 3.0V, 400 = 40.0V.

bbbb=0001-2500 indicates for output current 0.001A - 2.50A, the minimum step is 0.001A. e.g.: 0001=0.001A, 2500 =2.5A.

x= S, H, V or D which stands for different enclosure shape,
S stands for direct plug-in small enclosure,
H stands for direct plug-in horizontal enclosure,
V stands for direct plug-in vertical enclosure,
D stands for direct plug-in detachable plug enclosure,

yy=Blank, Blank means America fixed plug,

z= Blank , U, T or D which stands for different output port type,
U represent output interface type is USB for one port,
T represent output interface type is USB for two port,
D represent output interface type is DC wire, when x=D or V,
Blank represent output interface type is DC wire, when x=S or H.

C020n-mm

n=3,4,5,6,7,8,9, Which stands for marking Purpose

mm=US, Which stands for different plug type;
US means America Fixed plug



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

